

WHAT IS CLAIMED IS:

1. A hanging device, comprising:

a main body;

a clamping plate pivotally mounted on the main body;

5 a receiving chamber formed between the main body and the clamping plate; and

a press plate pivotally mounted on the main body and locked on the clamping plate to fix the clamping plate on the main body.

2. The hanging device in accordance with claim 1, wherein the main
10 body has two sides each formed with a protruding flange.

3. The hanging device in accordance with claim 1, wherein the main body has an inside formed with a plurality of receiving grooves for mounting a plurality of anti-skid pads.

4. The hanging device in accordance with claim 1, wherein the
15 clamping plate has an inside formed with a plurality of receiving grooves for mounting a plurality of anti-skid pads.

5. The hanging device in accordance with claim 1, wherein the main body has a first end formed with two spaced pivot bases each formed with a pivot hole, and the clamping plate has a first end formed with two spaced pivot
20 ears each pivotally mounted on a respective one of the two spaced pivot bases of the main body and each formed with a wedge-shaped locking stub pivotally mounted in the pivot hole of the respective pivot base of the main body.

6. The hanging device in accordance with claim 1, wherein the main body has a second end formed with two spaced pivot seats each formed with a pivot hole, and the press plate has a first end formed with two spaced pivot ears each pivotally mounted on a respective one of the two spaced pivot seats of the main body and each formed with a wedge-shaped locking stub pivotally mounted in the pivot hole of the respective pivot seat of the main body.

7. The hanging device in accordance with claim 1, wherein the clamping plate has a second end rested on a second end of the main body and formed with a locking hook, and the press plate has a mediate portion mounted on the locking hook of the clamping plate and formed with a locking groove for locking the locking hook of the clamping plate.

8. The hanging device in accordance with claim 7, wherein the mediate portion of the press plate is formed with an opening communicating with the locking groove for receiving the locking hook of the clamping plate.

9. The hanging device in accordance with claim 1, wherein the press plate has a second end formed with a press portion rested on the mediate portion of the clamping plate.

10. The hanging device in accordance with claim 9, wherein the clamping plate has a mediate portion formed with a blind hole for mounting a noise suppression pad, and the press portion of the press plate is located adjacent to the noise suppression pad.